



**AVAILABLE FINISHES:**  
**CA**

**AVAILABLE OPTIONS:**  
**EA** - Electrical Actuator  
**FL** - Fire Label  
**FX** - Integral Intumescent

**LS** - Lead Shields  
**PULL** - Pull Out  
**PV** - Pivot Doors  
**SF** - Security Fasteners  
**SL** - Sliding Doors  
**TD** - Top Door Installation

LEGACY	NGP	PEMKO	ZERO
7463	522N	434APKL	364AA

**AVAILABLE SIZES:** Can be manufactured to any length from 12" to 144"

**PRODUCT NOTES:**

- Adjusting the brass nut changes pressure on concealed internal spring to satisfy field conditions.
- Self-leveling door seal up to maximum 1" drop.
- Replacement closed cell sponge neoprene - Part #4563N
- Unit supplied standard with 1 pair of end caps - Part #4063EC-CA #4063EC-MB.

**PRODUCT KEY**

CA - Clear Anodized | MA - Mill Aluminum | BK - Black Anodized | DB - Dark Bronze Anodized | GD - Gold Anodized Aluminum | MB - Matte Black Powder Coat | WP - White Powder Coat | BR - Architectural Bronze | ORB - Oil Rubbed Bronze | POL - Polished Bronze | SP - Gray Steel Prime | SS - Stainless Steel



**FIRE**



**ACOUSTIC**

**SMS** - Sheet Metal Screw

**Project :**

**Submitted By :**

**Date :**

**Notes :**

**Company Name :**