



**AVAILABLE FINISHES:**  
CA, BK, DB, GD, WP

**AVAILABLE OPTIONS:**

**EA** - Electrical Actuator  
**EMI/RFI** - Electromagnetic/Radio Frequency Interference

**FL** - Fire Label  
**FX** - Integral Intumescent  
**LS** - Lead Shields

**PULL** - Pull Out  
**PV** - Pivot Doors  
**SF** - Security Fasteners  
**SL** - Sliding Doors

LEGACY	NGP	PEMKO	ZERO
7563-EMI	520N	4301APKL	365AA

**AVAILABLE SIZE:** Can be manufactured to any length from 12" to 144"

**PRODUCT NOTES:**

- Adjusting the brass nut changes pressure on concealed internal spring to satisfy field conditions.
- Self-leveling door seal up to maximum 1" drop.
- Replacement neoprene - Part #4563N
- Unit supplied standard with 1 pair of end caps - Part #4163EC-CA or #4163EC-MB.

**PRODUCT KEY**

CA - Clear Anodized | MA - Mill Aluminum | BK - Black Anodized | DB - Dark Bronze Anodized | GD - Gold Anodized Aluminum | MB - Matte Black Powder Coat | WP - White Powder Coat | BR - Architectural Bronze | ORB - Oil Rubbed Bronze | POL - Polished Bronze | SP - Gray Steel Prime | SS - Stainless Steel



**FIRE**



**ACOUSTIC**



**EMI / RF SMS** - Sheet Metal Screw

Project :

Submitted By :

Date :

Notes :

Company Name :