



**FINISHES: CA**

**AVAILABLE SIZES:** Can be manufactured to any length from 12" to 144"

**OPTIONS:**

- |                                 |                          |                                   |
|---------------------------------|--------------------------|-----------------------------------|
| <b>AIR</b> - Air Flow           | <b>LS</b> - Light Spring | <b>SF</b> - Security Fasteners    |
| <b>FL</b> - Fire Label          | <b>PULL</b> - Pull       | <b>SL</b> - Sliding Doors         |
| <b>EA</b> - Electrical Actuator | <b>PV</b> - Pivot Doors  | <b>TD</b> - Top Door Installation |

**NOTES:**

- Adjusting the brass nut changes pressure on concealed internal spring to satisfy field conditions.
- Self-leveling door seal up to maximum 5/8" drop.
- Replacement neoprene - Part #4023N
- Unit supplied with 1 pair of end caps - Part #4063EC-CA or #4063EC-MB

LEGACY	NGP	PEMKO	ZERO
<b>7023</b>	335N	411ARL	320AA

**ABBREVIATIONS & SYMBOLS KEY**

CA - Clear Anodized Aluminum | MA - Mill Aluminum | BR - Architectural Bronze  
 DB - Dark Bronze Anodized Aluminum | MB - Matte Black Powder Coat | WP - White Powder Coat

**N** - Neoprene

**SMS** - Sheet Metal Screw



**FIRE**

<b>Project :</b>	<b>Submitted By :</b>
<b>Date :</b>	<b>Notes :</b>
<b>Company Name :</b>	