



FINISHES: MA

AVAILABLE SIZES: Can be manufactured to any length from 12" to 144"

OPTIONS:

- AIR** - Air Flow
- EA** - Electrical Actuator
- FL** - Fire Label
- LIG** - Ligature Resistant
- LS** - Light Spring
- PV** - Pivot Doors
- NIT** - Nitrile Extrusion
- SF** - Security Fasteners
- SL** - Sliding Doors
- TD** - Top Door Installation

NOTES:

- For use on 1-3/4" and larger Hollow Metal doors
- Adjusting the brass nut changes pressure on concealed internal spring to satisfy field conditions.
- Self-leveling door seal up to maximum 1/2" drop.
- Replacement neoprene - Part #4075N
- No end caps provided

LEGACY	NGP	PEMKO	ZERO
7553	320N	420APK	355A

ABBREVIATIONS & SYMBOLS KEY

CA - Clear Anodized Aluminum | MA - Mill Aluminum | BR - Architectural Bronze
 DB - Dark Bronze Anodized Aluminum | MB - Matte Black Powder Coat | WP - White Powder Coat

SRE - Solid Rubber Extrusion **SMS** - Sheet Metal Screw
NRR - Noise Reduction Rubber



Project :	Submitted By :
Date :	Notes :
Company Name :	