



AVAILABLE FINISHES:
MA

AVAILABLE OPTIONS:
EA - Electrical Actuator
FL - Fire Label
LS - Lead Shields

PULL - Pull Out
PV - Pivot Doors
SF - Security Fasteners
SL - Sliding Doors
TD - Top Door Installation

LEGACY	NGP	PEMKO	ZERO
71553	-	-	3551A

AVAILABLE SIZES: Can be manufactured to any length from 12" to 144"

PRODUCT NOTES:

- For use on $1\frac{3}{4}$ " and larger Hollow Metal doors
- Adjusting the brass nut changes pressure on concealed internal spring to satisfy field conditions.
- Self-leveling door seal up to maximum $1\frac{1}{2}$ " drop.
- Replacement neoprene - Part #434N
- No end caps provided

PRODUCT KEY

CA - Clear Anodized | MA - Mill Aluminum | BK - Black Anodized | DB - Dark Bronze Anodized | GD - Gold Anodized Aluminum | MB - Matte Black Powder Coat | WP - White Powder Coat | BR - Architectural Bronze | ORB - Oil Rubbed Bronze | POL - Polished Bronze | SP - Gray Steel Prime | SS - Stainless Steel



FIRE



ACOUSTIC

SMS - Sheet Metal Screw

Project :	Submitted By :
Date :	Notes :
Company Name :	