



AVAILABLE FINISHES:

MA - Mill Aluminum

AVAILABLE OPTIONS:

AIR - Air Flow
EA - Electrical Actuator
FL - Fire Label
LS - Light Spring

LIG - Ligature Resistant
PV - Pivot Doors
SF - Security Fasteners
SL - Sliding Doors
TD - Top Door Installation

LEGACY	NGP	PEMKO	ZERO
72553	-	-	3552A

AVAILABLE SIZES: Can be manufactured to any length from 12" to 144"

PRODUCT NOTES:

- For use on 1-3/4" and larger Hollow Metal doors
- Adjusting the brass nut changes pressure on concealed internal spring to satisfy field conditions.
- Self-leveling door seal up to maximum 1/2" drop.
- Replacement Nylon Brush - Part #4075NB
- No end caps provided

PRODUCT KEY

BK - Black Anodized | BR - Architectural Bronze | CA - Clear Anodized | DB - Dark Bronze Anodized | GD - Gold Anodized Aluminum | MA - Mill Aluminum | MB - Matte Black Powder Coat | WP - White Powder Coat | SP - Gray Steel Prime | SS - Stainless Steel
SMS - Sheet Metal Screw

Project :	Submitted By :
Date :	Notes :
Company Name :	